

# TradeWinds International, Inc.

## KRYSTALKOTE™

### Limited Warranty of Performance

**TradeWinds International, Inc.**, hereby offers a limited warranty of performance on **KrystalKote™**, a two-component, US DA- & CalTrans-Approved, EPA & SCAQMD VOC-compliant, high-solids, anti-graffiti, aliphatic polyurethane coating, according to the following criteria:

- A. Adherence to conditions and directions, as described in the **KrystalKote™ Data Sheet**, concerning proper surface preparation; material mixing & application; and observation of proper cure time, prior to allowable use conditions.
- B. Exposure to U-V, weather, limited chemical & physical contact, and normal conditions of use, with noted restrictions and qualifications, as described in the **KrystalKote™ Data Sheet**.
- C. Quality of application, quality of components, chemical make-up and physical condition of any underlying coatings, whether previously or newly applied, must be thoroughly tested and documented, for proper compatibility, prior to any proposed overlaying application of **KrystalKote™**. Any and all evidence of non-compatibility, poor condition of undercoat, or lack of proper surface preparation, gathered prior or subsequent to over-coating, will void any suggested, implied, or written warranty concerning any overlaying application of **KrystalKote™**.

**TradeWinds International, Inc.**, with above cited qualifications and conditions, hereby warrants the following guarantees of performance, with liability not to exceed the warranted product replacement cost or actual replacement of the warranted product:

1. **KrystalKote™/KrystalTred™ Custom gloss, semi-gloss, satin, or flat** finishes, are warranted against fading (loss of color) greater than ten percent (10%) of original color tone or hue, due to U-V exposure and normal effects of weathering, for a period of ten (10) years.
2. **KrystalKote™ Clear gloss** is also warranted to protect underlying color coats from fading (loss of color) greater than ten percent (10%) of original color tone or hue, due to U-V exposure and normal effects of weathering, for a period of ten (10) years. **KrystalKote™ Clear gloss** is further warranted against noticeable yellowing from U-V exposure, for a period of ten (10) years.