

## COVERAGE:

**QuartzBase™** (as **basecoat** on porous concrete):  
100 sq.ft./gallon at **15-mil WFT** (1/64-inch) to  
27 sq.ft./gallon at **60-mil WFT** (1/16-inch).

**QuartzKote™** (as *slip-resistant topcoat* over color-blended quartz aggregate):  
200 sq.ft./gallon at **5-mil DFT** (6-mil WFT);

or

**QuartzKote™** (as *smooth topcoat* over *rub-brick prepared* color-blended quartz aggregate):  
100 sq.ft./gallon at **10-mil DFT** (12-mil WFT) [applied in two separate coats];

or

**QuartzBase™** (as *slip-resistant topcoat* over color-blended quartz aggregate):  
250 sq.ft./gallon at **6-mil DFT** (6-mil WFT).

or

**QuartzBase™** (as *smooth topcoat* over *rub-brick prepared* color-blended quartz aggregate):  
100 sq.ft./gallon at **15-mil DFT** (15-mil WFT) [applied in single coat].

**Color-Blended Quartz Aggregate** manufacturers usually recommend 1-lb aggregate/sq.ft.

## COST:

**QuartzBase™** (as *basecoat*)  
at **100 sq.ft./gallon** [list: \$85/gal] [dist: \$68/gal = **68¢/sq.ft.**] {standard}  
at **27 sq.ft./gallon** [list: \$85/gal] [dist: \$68/gal = **\$2.52/sq.ft.**] {thick}

**QuartzKote™** (as *topcoat*)  
at **200 sq.ft./gallon** [list: \$93/gal] [dist: \$74/gal = **37¢/sq.ft.**] {slip-resistant}  
at **100 sq.ft./gallon** [list: \$93/gal] [dist: \$74/gal = **74¢/sq.ft.**] {smooth}

or

**QuartzBase™** (as *topcoat*)  
at **250 sq.ft./gallon** [list: \$85/gal] [dist: \$68/gal = **27¢/sq.ft.**] {slip-resistant}  
at **100 sq.ft./gallon** [list: \$85/gal] [dist: \$68/gal = **68¢/sq.ft.**] {smooth}

Standard **QuartzFloor™** *Distributor* materials cost:  $68¢ + 37¢ = \$1.05/\text{sq.ft.}$  {slip-resistant}  
 $68¢ + 74¢ = \$1.42/\text{sq.ft.}$  {smooth}